

Bond | Protect | Beautify

www.sames-kremlin.com



Equipment

| Designation | Part number |
|--|-------------|
| Pack Inogun A, Inocontroller, pump, bar, 20 m | 910028695 |
| Pack Inogun A FCC, Inocontroller, pump, tube, 30 m | 910028696 |
| Pack Inogun A, Inocontroller, pump, bar, 20 m | 910030624 |
| Pack Inogun A FCC, Inocontroller, tube, 30 m | 910030625 |
| Pack Inogun A, Inobox NF, pump, bar, 20 m | 910030626 |
| Pack Inogun A FCC, Inobox NF, pump, tube, 30 m | 910030577 |
| Pack Inogun A, Inobox, bar, NDT | 910030061 |
| Pack Inogun A FCC, Inobox, tube, NDT | 910030062 |
| Inogun A, cable 20 m, bar | 910028713 |
| Inogun A FCC, cable 30 m, tube | 910028715 |

SAMES  **KREMLIN**

INOGUN A and A FCC

Automatic powder gun

Powder / Automatic Guns



MODULAR DESIGN FOR FLEXIBLE INTEGRATION AND PROCESS EVOLUTION

- Lifetime finish quality: Long life cascade durability and HV performance**
- Efficient powder transfer: TEC5 technology**
- Reduced downtime: Quick gun change in less than 1 minute**



SAMES  **KREMLIN**

13 chemin de Malacher - CS 70086
38243 MEYLAN Cedex - FRANCE
Phone: +33 (0)4 76 41 60 60 - Fax: +33 (0)4 76 41 60 90

202103 - 573.800.002 (NA# 999.600.424)

Airless® is a registered trademark : FR n° 1 222 301
SAMES KREMLIN reserves the right to modify its equipment or specifications without further notice. Document, products and pictures shown are not contractual.

Apply your Skills

www.sames-kremlin.com

Markets



INOGUN A and A FCC

Automatic powder gun

The Inogun A or Inogun A FCC sprayer gather all SAMES KREMLIN's knowledge and expertise to provide the best electrostatic technology for the application of powder in automatic booths.

The **Inogun range** is built upon a common base, thoroughly tested, and available with different fixing gear according to needs in the powder booth: the **Inogun A** rear fitted flange to be tilted towards the parts and the **Inogun A FCC** (Fast Color Change) with its smooth droplet shape for easy color changes.

Powder and energy savings have been placed at the heart of the gun for reducing waste, enhancing productivity, and finishing quality of the coating. The powerful High Voltage unit paired with the high voltage control unit produces a high wraparound effect on big parts (D. 500mm / 20 in), as well as a deep penetration in recessed areas. It greatly helps to reduce the running cost of the equipment with a better powder use rate and significantly reduces the pre-touch or touch-up actions. The smoothly-shaped parts, inside and outside the gun, make color change faster.

Should it be used in an advanced powder process or in a very simple, performing powder booth, it may be controlled either by the connected built-in Inocontroller or the Inobox equipped with a user-friendly and clear interface. Both are the brain of the Inogun and feature High Voltage and all air controls: high voltage, current, electrode cleaning air, injection, and dilution.



Technical data table

| Designation | Value | Unit: metric (US) |
|-----------------------------------|------------------------|-------------------|
| Maximum Air Pressure | 7 (101.5) | bar (psi) |
| Air Consumption | 2 - 10 (1.2 - 5.9) | m3/h (cfm) |
| High Voltage (maximum) | 100 | kV |
| Current Max | 110 | µA |
| Powder Output Max | 450 (63.7) | g/mn (oz/mn) |
| Air Supply Pressure | 7 (101.5) | bar (psi) |
| Relative Humidity Max | 80 | % |
| Length (gun only) | 460 (18.1) | mm (in) |
| Length INOGUN - bar diameter | 1046 - 30 (41.2 - 1.2) | mm + mm (in + in) |
| Length INOGUN FCC - tube diameter | 1423 - 40 (56 - 1.6) | mm + mm (in + in) |
| Width | 49 (1.9) | mm (in) |
| Height | 69 (2.7) | mm (in) |
| Weight | 650 (23) | g (oz) |


Technologies



TEC5



FCC Technology



Corona Charge

PERFORMANCE

- 1 Easy and accurate settings for voltage and current
- 2 Constant and stable spray for a smooth and even application
- 3 TEC5 technology offers a high-quality finish
 - ◆ Fast color change without cross-contamination

PRODUCTIVITY

- 3 High transfer efficiency to reduce additional manual work
- 4 Wide range of adapted nozzles for optimal application
- 5 Powerful cascade providing a strong wraparound effect
- 6 Advanced HV control for excellent penetration in recessed areas
- 6 Widest fieldbus communication protocols for the INOCONTROLLER
 - ◆ Modular gun design for an easy integration

SUSTAINABILITY

- 4 Highly abrasion-resistant nozzles
- 5 Heavy-duty electrostatic cascade
- 7 Quick disconnect in 1 minute, only 1 operator needed to change gun
 - ◆ Robust design
 - ◆ 2+1 years warranty *

* except wearable parts, see conditions to apply on the [warranty page](#) of our web site

Description

